

Single Phase Inverter with HD-Wave Technology

For Australia

SE3000H, SE4000H, SE5000H, SE6000H, SE8000H,
SE10000H

INVERTERS



Optimised installation with HD-Wave technology

- Specifically designed to work with power optimisers
- Quick and easy inverter commissioning directly from a smartphone using the SolarEdge SetApp
- Record-breaking efficiency
- Extremely small, lightweight and easy to install
- High reliability
- Built-in module-level monitoring
- Outdoor and indoor installation
- Fixed voltage inverter for longer strings
- Advanced safety features - integrated arc fault protection

/ Single Phase Inverter with HD-Wave Technology For Australia

SE3000H, SE4000H, SE5000H, SE6000H, SE8000H, SE10000H

APPLICABLE TO INVERTERS WITH PART NUMBER	SE3000H	SE4000H	SE5000H	SE6000H	SE8000H	SE10000H	
	SEXXXXH-AUXXXBXX4						
OUTPUT							
Rated AC Power Output	3000	4000	5000	6000	8000	10000	VA
Maximum AC Power Output	3000	4000	5000	6000	8000	10000	VA
AC Output Voltage (Nominal)	220/230						Vac
AC Output Voltage Range	184 - 264.5						Vac
AC Frequency (Nominal)	50/60 ± 5						Hz
Maximum Continuous Output Current	14	18.5	23	27.5	36.5	45.5	A
Total Harmonic Distortion (THD)	< 3						%
Power Factor	1, adjustable -0.8 to 0.8						
Utility Monitoring, Islanding Protection, Configurable Power Factor, Country Configurable Thresholds	Yes						
INPUT							
Maximum DC Power	4650	6200	7750	9300	12400	15500	W
Transformer-less, Ungrounded	Yes						
Maximum Input Voltage	480						Vdc
Nominal DC Input Voltage	380			400			Vdc
Maximum Input Current	9	11.5	13.5	16.5	20.5	25.5	Adc
Reverse-Polarity Protection	Yes						
Ground-Fault Isolation Detection	600kΩ sensitivity per unit						
Maximum Inverter Efficiency	99.2						%
European Weighted Efficiency	98.8		99				%
Nighttime Power Consumption	< 2.5						W
ADDITIONAL FEATURES							
Supported Communication Interfaces	RS485, Ethernet, ZigBee for Smart Energy (optional) ⁽¹⁾ , Wi-Fi (optional)						
Smart Energy Management ⁽²⁾	Export limitation						
Arc Fault Protection	Integrated, user configurable (according to UL1699B)						
Inverter Commissioning	With the SetApp mobile application using built-in Wi-Fi Access-Point for local connection						
STANDARD COMPLIANCE							
Safety	IEC62109, AS/NZS3100						
Grid Connection Standards	AS/NZS4777:2015						
Emissions	IEC61000-6-2, IEC61000-6-3, IEC61000-3-11, IEC61000-3-12, FCC Part 15 Class B						
INSTALLATION SPECIFICATIONS							
AC Output Conduit Size / Wire Cross Section	25mm maximum / 1-13 mm ²						
DC Input Conduit Size / # of Strings / Wire Cross Section	25mm maximum / 1-2 strings / 1-13 mm ²			25mm maximum / 1-3 strings / 1-13 mm ²			
Dimensions with Safety Switch (H x W x D)	450 x 370 x 174			540 x 370 x 185			mm
Weight with Safety Switch	10	11.4	11.9	17.6			kg
Noise	< 25			< 50			dBA
Cooling	Natural convection						
Operating Temperature Range	-40 to +60 ⁽³⁾						°C
Protection Rating	IP65 - outdoor and indoor						

(1) For more information refer to: <https://www.solaredge.com/sites/default/files/se-zigbee-plug-in-wireless-communication-for-setapp-datasheet-au.pdf>

(2) For export limitation, the optional export meter is required. This built-in meter can also be used for additional home energy management capabilities, if needed.

(3) Full power up to at least 50°C. For power de-rating information refer to: <https://www.solaredge.com/sites/default/files/se-temperature-derating-note.pdf>